



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) Publication number:

**0 488 307 A3**

(12)

## EUROPEAN PATENT APPLICATION

(21) Application number: 91120423.8

(51) Int. Cl.<sup>5</sup>: H01J 37/32, H01L 21/00

(22) Date of filing: 28.11.91

(30) Priority: 28.11.90 JP 331317/90

(43) Date of publication of application:  
03.06.92 Bulletin 92/23

(84) Designated Contracting States:  
DE FR GB IT NL

(88) Date of deferred publication of the search report:  
25.11.92 Bulletin 92/48

(71) Applicant: TOKYO ELECTRON LIMITED  
2-3-1, Nishi-Shinjuku  
Shinjuku-ku, Tokyo(JP)  
(84) DE FR GB IT NL

(71) Applicant: Kabushiki Kaisha Toshiba  
72, Horikawa-cho Saiwai-ku  
Kawasaki-shi(JP)  
(84) DE FR GB

(72) Inventor: Nozawa, Toshihisa, c/o Intellectual  
Property Div.

KABUSHIKI KAISHA TOSHIBA, 1-1 Shibaura  
1-chome  
Minato-ku, Tokyo 105(JP)  
Inventor: Arami, Junichi, c/o Intellectual  
Property Div.

KABUSHIKI KAISHA TOSHIBA, 1-1 Shibaura  
1-chome  
Minato-ku, Tokyo 105(JP)  
Inventor: Horioka, Keiji, c/o Intellectual  
Property Div.

KABUSHIKI KAISHA TOSHIBA, 1-1 Shibaura  
1-chome  
Minato-ku, Tokyo 105(JP)  
Inventor: Hasegawa, Isahiro, c/o Intellectual  
Property Div.  
KABUSHIKI KAISHA TOSHIBA, 1-1 Shibaura  
1-chome  
Minato-ku, Tokyo 105(JP)

(74) Representative: Lehn, Werner, Dipl.-Ing. et al  
Hoffmann, Eitle & Partner Patentanwälte  
Arabellastrasse 4  
W-8000 München 81(DE)

(54) Plasma etching apparatus.

(57) A plasma etching apparatus comprising a susceptor (12, 14) for holding a semiconductive wafer, a cooling jacket (20) having a coolant (21) of a large cooling capacity and capable of quickly cooling said susceptor (12, 14) to an intended low temperature, a process chamber (10a) enclosing the susceptor (12, 14) and the cooling jacket (20), a gas discharging mechanism (34, 36) for evacuating the process chamber (10a), an insulating member (16) inter-

posed between the susceptor (12, 14) and the cooling jacket (20), a gas supply device (71, 80) for supplying gas to an O-ring holding groove (51, 53, 55) arranged on the interface regions (59) of the susceptor (12, 14), the insulating member (16) and the cooling section (20) and a pressure control mechanism (70) for controlling the pressure of the supplied gas.

EP 0 488 307 A3




FIG. 1



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number

EP 91 12 0423

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	DATABASE WPIL Week 8949, Derwent Publications Ltd., London, GB; AN 89-359386 & JP-A-1 268 030 (HITACHI) * abstract * & US-A-5 085 750 (SORAOKA) * column 3, line 19 - column 4, line 48; figure 1 * ---	1,2	H01J37/32 H01L21/00
A	EP-A-0 339 580 (APPLIED MATERIALS INC) * column 16, line 9 - column 18, line 5; figure 7 * -----	1	
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			H01L H01J
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 28 SEPTEMBER 1992	Examiner BOLDER G.
<b>CATEGORY OF CITED DOCUMENTS</b> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons * : member of the same patent family, corresponding document			

EPO FORM 1500 (03.82) (P0401)